

Combistrip 24



Recommendation: for entrances with a modern design

Materials:

Aluminium profiles with grooved side bars. Grooved rubber strips with a high wiping effect.

Variations:

- ➤ gap between profiles 5 or 10 mm
- ➤ with snow scraper bar
- reinforced model with full hard plastic core available upon request.

Colours:

as shown on left page.

Features:

Weatherproof. Ideal for removing coarse dirt. Sound insulated and slip-resistant due to underlaid rubber strips.

Fire resistance: classified as Cfl-s1 according to the fire safety standards EN 11925-2 and EN 9239-1 (corresponds to B1, Q1 according to former Austrian standards [ÖNORM])

Dimensions:

Height: 24 mm

gap between profiles: approx. 5 mm or 10 mm

Profile length: max. 2 m - longer mats are designed

in two or more parts.

Large mats also have to be designed in two or three parts in the direction of traffic. If the mat is self-supporting, a cross bar has to be inserted at least every 40 cm.

Standard sizes (dimensions of complete mat):

59 x 39 cm, 79 x 49 cm (gap between profiles 10 mm) Standard colours black and grey.

Shapes

Any shape of mat is possible



Weight:

approx. 15 kg/m²

Cleaning:

Simply vacuum surface and floor below (ideally every day). In the case of heavy soiling hose down with a strong water jet (e. g. high pressure washer).

Specification:

Supply and install **HAGOMAT Combistrip 24**, Ref. No... with grooved side bars and grooved rubber inserts. Colour of the rubber strips... Made to measure without compensating end profiles. Fire rating: Cfl-s1.



Available colours:



_	J		

Ref. No.	Туре	Approx. height	Inside height of angle frame required (see page 7)
11 300	Hagomat Combistrip 24 gap between profiles 5 mm	24 mm	23 mm
11 310	Hagomat Combistrip 24 gap between profiles 10 mm	24 mm	23 mm
11 302	Hagomat Combistrip 24 with snow scraper bar	24 mm	23 mm

A **reinforced version** of Combistrip 24 is also available. (See also page 5 and price list.)